



Number	109378/01	Replaces	--
Issued	15/11/2021	Scope	AR 209
Contract number	Q96/015	Page	1-4

Product Certificate

Steel press fittings for steel pipes

Based on pre-certification tests as well as periodic inspections by Kiwa Nederland B.V., the products referred to in this certificate and marked with the GASTEC QA mark, supplied by

Aalberts integrated piping systems B.V.

may, on delivery, be relied upon to comply with the GASTEC QA Approval Requirements 209, for "Steel press fittings for steel pipes", dated May 2019.

Ron Scheepers
Kiwa

This certificate is issued by Kiwa Nederland B.V. in conjunction with the KIWA regulations for Certification 2017.

This certificate consists of 4 pages.
Publication of the certificate is allowed.

Kiwa Nederland B.V.
Sir. Winston Churchillaan 273
P.O. Box 70
2280 AB RIJSWIJK
The Netherlands
Tel.+31 88 998 4400
Nl.kiwa.info@kiwa.com
www.kiwa.nl

supplier

Aalberts integrated piping systems B.V.
Oude Amersfoortseweg 99
1212 AA Hilversum
The Netherlands

www.aalberts-ips.nl

T +31 35 6884 211



Number	109378/01	Replaces	--
Issued	15/11/2021	Scope	AR 209
Contract number	Q96/015	Page	2-4

Steel press fittings for steel pipes

PRODUCT SPECIFICATION

VSH PowerPress fittings

Maximum operating pressure: 5 bar

VSH PowerPress straight coupling FF 1 1/2"
VSH PowerPress straight coupling FF 1 1/4"
VSH PowerPress straight coupling FF 1"
VSH PowerPress straight coupling FF 1/2"
VSH PowerPress straight coupling FF 2"
VSH PowerPress straight coupling FF 3/4"

VSH PowerPress slip coupling FF 1 1/2"
VSH PowerPress slip coupling FF 1 1/4"
VSH PowerPress slip coupling FF 1"
VSH PowerPress slip coupling FF 1/2"
VSH PowerPress slip coupling FF 2"
VSH PowerPress slip coupling FF 3/4"

VSH PowerPress reducer FØ 1 1/2"xØ2"
VSH PowerPress reducer FØ 1 1/4"xØ1 1/2"
VSH PowerPress reducer FØ 1 1/4"xØ2"
VSH PowerPress reducer FØ 1"xØ1 1/2"
VSH PowerPress reducer FØ 1"xØ1 1/4"
VSH PowerPress reducer FØ 1"xØ2"
VSH PowerPress reducer FØ 1/2"xØ1 1/2"
VSH PowerPress reducer FØ 1/2"xØ1 1/4"
VSH PowerPress reducer FØ 1/2"xØ1"
VSH PowerPress reducer FØ 1/2"xØ2"
VSH PowerPress reducer FØ 1/2"xØ3/4"
VSH PowerPress reducer FØ 3/4"xØ1 1/2"
VSH PowerPress reducer FØ 3/4"xØ1 1/4"
VSH PowerPress reducer FØ 3/4"xØ1"
VSH PowerPress reducer FØ 3/4"xØ2"

VSH PowerPress bend 45° FØ 1 1/2"
VSH PowerPress bend 45° FØ 1 1/4"
VSH PowerPress bend 45° FØ 1"
VSH PowerPress bend 45° FØ 1/2"
VSH PowerPress bend 45° FØ 2"
VSH PowerPress bend 45° FØ 3/4"
VSH PowerPress bend 45° FF 1 1/2"
VSH PowerPress bend 45° FF 1 1/4"
VSH PowerPress bend 45° FF 1"
VSH PowerPress bend 45° FF 1/2"
VSH PowerPress bend 45° FF 2"
VSH PowerPress bend 45° FF 3/4"

VSH PowerPress straight connector FF 1 1/2"xRp1 1/2"
VSH PowerPress straight connector FF 1 1/4"xRp1 1/4"
VSH PowerPress straight connector FF 1"xRp1"
VSH PowerPress straight connector FF 1/2"xRp1/2"
VSH PowerPress straight connector FF 2"xRp2"
VSH PowerPress straight connector FF 3/4"xRp3/4"

VSH PowerPress straight connector FM 1 1/2"xR1 1/2"
VSH PowerPress straight connector FM 1 1/4"xR1 1/4"
VSH PowerPress straight connector FM 1"xR1"
VSH PowerPress straight connector FM 1/2"xR1/2"
VSH PowerPress straight connector FM 2"xR2"
VSH PowerPress straight connector FM 3/4"xR3/4"

VSH PowerPress bend 90° FF 1 1/2"
VSH PowerPress bend 90° FF 1 1/4"
VSH PowerPress bend 90° FF 1"
VSH PowerPress bend 90° FF 1/2"
VSH PowerPress bend 90° FF 2"
VSH PowerPress bend 90° FF 3/4"
VSH PowerPress bend 90° FØ 1 1/2"
VSH PowerPress bend 90° FØ 1 1/4"
VSH PowerPress bend 90° FØ 1"
VSH PowerPress bend 90° FØ 1/2"
VSH PowerPress bend 90° FØ 2"
VSH PowerPress bend 90° FØ 3/4"

VSH PowerPress T-piece FFF 1 1/2"
VSH PowerPress T-piece FFF 1 1/4"
VSH PowerPress T-piece FFF 1"
VSH PowerPress T-piece FFF 1/2"
VSH PowerPress T-piece FFF 2"
VSH PowerPress T-piece FFF 3/4"

Number	109378/01	Replaces	--
Issued	15/11/2021	Scope	AR 209
Contract number	Q96/015	Page	3-4

Steel press fittings for steel pipes

VSH PowerPress reduced T-piece FFF 1 1/2"x1 1/2"x1 1/4"
VSH PowerPress reduced T-piece FFF 1 1/2"x1 1/2"x1"
VSH PowerPress reduced T-piece FFF 1 1/2"x1 1/2"x1/2"
VSH PowerPress reduced T-piece FFF 1 1/2"x1 1/2"x3/4"
VSH PowerPress reduced T-piece FFF 1 1/4"x1 1/4"x1"
VSH PowerPress reduced T-piece FFF 1 1/4"x1 1/4"x1/2"
VSH PowerPress reduced T-piece FFF 1 1/4"x1 1/4"x3/4"
VSH PowerPress reduced T-piece FFF 1"x1"x1/2"
VSH PowerPress reduced T-piece FFF 1"x1"x3/4"
VSH PowerPress reduced T-piece FFF 2"x2"x1 1/2"
VSH PowerPress reduced T-piece FFF 2"x2"x1 1/4"
VSH PowerPress reduced T-piece FFF 2"x2"x1"
VSH PowerPress reduced T-piece FFF 2"x2"x1/2"
VSH PowerPress reduced T-piece FFF 2"x2"x3/4"
VSH PowerPress reduced T-piece FFF 3/4"x3/4"x1/2"

VSH PowerPress flange adapter 1 1/2" DN40 PN10/16
VSH PowerPress flange adapter 1 1/4" DN32 PN10/16
VSH PowerPress flange adapter 2" DN50 PN10/16

VSH PowerPress reduced coupling FF 1"x1/2"
VSH PowerPress reduced coupling FF 1"x3/4"
VSH PowerPress reduced coupling FF 3/4"x1/2"

VSH PowerPress threaded T-piece FFF 1 1/2"x1 1/2"xRp1"
VSH PowerPress threaded T-piece FFF 1 1/2"x1 1/2"xRp1/2"
VSH PowerPress threaded T-piece FFF 1 1/2"x1 1/2"xRp3/4"
VSH PowerPress threaded T-piece FFF 1 1/4"x1 1/4"xRp1"
VSH PowerPress threaded T-piece FFF 1 1/4"x1 1/4"xRp1/2"
VSH PowerPress threaded T-piece FFF 1 1/4"x1 1/4"xRp3/4"
VSH PowerPress threaded T-piece FFF 1"x1"xRp1/2"
VSH PowerPress threaded T-piece FFF 1"x1"xRp3/4"
VSH PowerPress threaded T-piece FFF 1/2"x1/2"xRp1/2"
VSH PowerPress threaded T-piece FFF 2"x2"xRp1"
VSH PowerPress threaded T-piece FFF 2"x2"xRp1/2"
VSH PowerPress threaded T-piece FFF 2"x2"xRp3/4"
VSH PowerPress threaded T-piece FFF 3/4"x3/4"xRp1/2"

VSH PowerPress stop end F 1 1/2"
VSH PowerPress stop end F 1 1/4"
VSH PowerPress stop end F 1"
VSH PowerPress stop end F 1/2"
VSH PowerPress stop end F 2"
VSH PowerPress stop end F 3/4"

APPLICATION AND USE

Steel press fittings for use in combination with steel pipes in accordance with NEN-EN 10255, NEN-EN 10305-1/-2/-3, NEN-EN 10216-1, NEN-EN 10217-1 with a maximum pipe outer diameter of 114,3 mm (4").

The press fittings are intended to be used for indoor gas installations for 2nd and 3rd family gasses according to NEN-EN 437 with a maximum operation pressure of 5 bar (MOP) at an ambient temperature of -15 °C to +50 °C.

MARKING

- GASTEC QA, GASTEC QA logo or trademark..
- Name or trademark of manufacturer: VSH PowerPress
- External diameter of the pipe to be connected:
- Production date:
- The word GAS or a yellow marking
- Maximum operating pressure: MOP 5

Number	109378/01	Replaces	--
Issued	15/11/2021	Scope	AR 209
Contract number	Q96/015	Page	4-4

Steel press fittings for steel pipes

RECOMMENDATIONS FOR END USERS

Check at the time of delivery whether:

- the producer has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport.

Consult the producer's processing guidelines for the proper storage and transport methods.

Check whether this certificate is still valid by consulting Kiwa Nederland B.V. or the Kiwa website.

If you should reject a product on the basis of the above, please contact the supplier and, if necessary, Kiwa Nederland B.V.
